1.27MM PITCH FLAT CABLE EMI FERRITE CORES ONE PIECE TYPE

Fig.1



Fig.2



APPLICATIONS

- Internal floppy disk and harddisk ribbon cables
- Internal ribbon cables between circuit boards and date connectors
- Internal ribbon cables with series digital signal busses

Part No.	Fig.	Dimension					Impedance (Ω) Min	
		A	B	C	D	E	25MHz	100MHz
COREF-08A	1	16.0±0.5	12.0±0.4	5.0±0.3	11.5±0.4	0.85±0.2	35	95
COREF-10A	1	19.0±0.8	12.0±0.4	6.5±0.3	13.5±0.6	1.5±0.3	34	98
COREF-14A	1	23.8±0.6	15.0±0.5	6.3±0.3	18.8±0.5	1.1±0.3	40	90
COREF-16A	1	25.0±0.8	12.0±0.5	5.0±0.3	21.5±0.8	1.0±0.3	38	100
COREF-18A	2	28.0±0.8	14.6±0.5	7.7±0.4	23.0±0.8	1.5±0.3	45	90
COREF-20A	1	31.5±0.8	12.0±0.4	3.5±0.3	28.0±0.8	0.8±0.2	25	65
COREF-22C	1	33.0±0.8	11.5±0.4	7.5±0.4	28.0±0.8	2.8±0.3	40	95
COREF-21A	1	33.5±0.8	12.0±0.4	6.5±0.3	29.0±0.8	1.5±0.3	30	75
COREF-26A	1	40.0±1.0	12.0±0.4	6.5±0.3	35.0±1.0	1.3±0.3	35	88
COREF-30A	1	45.2±1.0	12.0±0.4	6.5±0.3	40.0±1.0	1.3±0.3	37	110
COREF-34A	1	49.6±1.2	12.0±0.4	6.5±0.3	44.0±1.0	1.3±0.3	25	70
COREF-40A	1	57.6±1.2	12.0±0.4	6.5±0.3	52.0±1.0	1.3±0.3	30	75

ORDERING INFORMATION:

P/N C O R E F - $\frac{x\,x}{1}\,\frac{x}{2}$

1. NO. OF CONTACTS OF FLAT CABLE:
   08, 10, 14, 16, 18, 20, 21, 22, 26, 30, 34, 40
2. SPECIAL CODE:
   A, B, C, ...etc.

tel. 02.3361.1626 info@elitaliaweb.it
fax 02.2626.1009 www.elitaliaweb.it