



## LOCK LEVER CONNECTORS

## LL600-221

| FEATURE   | LL600-221-102   |             | LL600-221-103   |             |
|---|---|-------------|---|-------------|
| <ul style="list-style-type: none"> <li>* Splicing function</li> <li>* 2-3 conductor connector</li> <li>* With operating lock levers</li> <li>* 4mm<sup>2</sup> cross section</li> </ul> |  |             |  |             |
| REFERENCE STANDARD  | UL  | IEC         | UL  | IEC         |
| RATED VOLTAGE (V)   | 660   | 450         | 660   | 450         |
| RATED CURRENT (A)   | 20  | 32          | 20  | 32          |
| WIRE DIAMETER (AWG/mm <sup>2</sup> )  | 24-12   | 0,14(0,2)-4 | 24-12   | 0,14(0,2)-4 |
| VOLTAGE RESISTANCE (Kv)   | 2,5   |             | 2,5   |             |
| MECHANICAL PROPERTIES   | -   |             | -   |             |
| AMBIENT TEMPERATURE (°C)  | -40~+105  |             | -40~+105  |             |
| STRIP LENGHT (mm)   | 11  |             | 11  |             |
| L/W/H (mm)  | 18,2 x 13 x 9,8   |             | 18,2 x 18,6 x 9,8   |             |
| NUMBER OF POLES (p)   | 2   |             | 3   |             |
| MATERIAL AND PLATING  | -   |             | -   |             |
| PLASTIC PARTS   | PC, UL94, V-2   |             | PC, UL94, V-2   |             |
| SHRAPNEL CONTACT  | stainless steel   |             | stainless steel   |             |
| CONTACT MATERIAL  | electrolytic copper nickel tin  |             | electrolytic copper nickel tin  |             |