



RM-F series

RM-K series

RM-U series

Push-Pull Self-Latching system	Push-Pull Self-Latching system	Push-Pull Self-Latching system
Shell size:0F,1F,AF,2F,3F	Shell size:0K,1K,2K,3K	Shell size:0U,1U
Multipole contacts:2-19 contacts	Multipole contacts:2-32 contacts	Multipole contacts:2-19 contacts
Natural and Black Chrome Plated Brass	Natural and Black Chrome Plated Brass	Natural and Black Chrome Plated Brass
OEM / ODM	OEM / ODM	OEM / ODM
CE,SGS,ROHS,ISO9001:2015	CE,SGS,ROHS,ISO9001:2015	CE,SGS,ROHS,ISO9001:2015
Temperature range:-55°C~250°C	Temperature range:-55°C~250°C	Temperature range:-55°C~250°C
Various contact types:Straight solder, Print and Elbow print 90°	Various contact types:Straight solder, Print and Elbow print 90°	Various contact types:Straight solder, Print and Elbow print 90°
360°screening for full EMC shielding	360°screening for full EMC shielding	360°screening for full EMC shielding
IP68	IP68	IP68
Cable diameter:1-10mm	Cable diameter:1-11mm	Cable diameter:1-10mm



RM-V series

RM-T series

RM-E series

Screw Locking System	Push-Pull Self-Latching system	Push-Pull Self-Latching system
Shell size:0V,1V,2V	Shell size:0T	Shell size:1E
Multipole contacts:2-26 contacts	Multipole contacts:2-9contacts	Multipole contacts:1-6 contacts
Natural and Black Chrome Plated Brass	Natural and Black Chrome Plated Brass	Natural and Black Chrome Plated Brass
OEM / ODM	OEM / ODM	OEM / ODM
CE,SGS,ROHS,ISO9001:2015	CE,SGS,ROHS,ISO9001:2015	CE,SGS,ROHS,ISO9001:2015
Temperature range:-55°C~250°C	Temperature range:-55°C~250°C	Temperature range:-55°C~250°C
Various contact types:Straight solder, Print and Elbow print 90°	Various contact types:Straight solder, Print and Elbow print 90°	Various contact types:Straight solder and Print and Elbow print 90°
360°screening for full EMC shielding	360°screening for full EMC shielding	360°screening for full EMC shielding
IP68	IP68	IP68
Cable diameter:1-8mm	Cable diameter:1-5mm	Cable diameter:1-7mm



RM-M series



RM-M16 series



RM-B series

Bayonet locking system	Screw Locking system	Push-Pull Self-Latching system
Shell size:3M	Shell size: M16	Shell size:00B,0B,1B,2B,3B
Multipole contacts: 2-30 contacts	Multipole contacts:3-12 contacts	Multipole contacts:2-32 contacts
Aluminum with Gun-metal colour Plated	Brass with nickel plated	Natural and Black Chrome Plated Brass
OEM / ODM	OEM / ODM	OEM / ODM
CE,SGS,ROHS,ISO9001:2015	CE,SGS,ROHS,ISO9001:2015	CE,SGS,ROHS,ISO9001:2015
Temperature range:-55°C~250°C	Temperature range:-40°C~85°C	Temperature range:-55°C~250°C
Various contact types:Straight solder, Print and Elbow print 90°	Various contact types:Straight solder and Print Elbow print 90°	Various contact types:Straight solder, Print and Elbow print 90°
360°screening for full EMC shielding	360°screening for full EMC shielding	360°screening for full EMC shielding
IP68	IP40	IP50
Cable diameter:1-7mm	Cable diameter:1-8mm	Cable diameter:1-11mm



RM-S series



RM-P series



RM-H series

Push-Pull Self-Latching system	Push-Pull Self-Latching system	Push-Pull Self-Latching system
Shell size:00,0S,1S,2S	Shell size:1P	Shell size:7#,10#,12#
Multipole contacts:1-10 contacts	Multipole contacts:2-14 contacts	Multipole contacts:4-20 contacts
Natural and Black Chrome Plated Brass	Colorful identification(Grey,Red,Blue,Green, Yellow,White and Black)	Brass with nickel plated
OEM / ODM	OEM / ODM	OEM / ODM
CE,SGS,ROHS,ISO9001:2015	CE,SGS,ROHS,ISO9001:2015	CE,SGS,ROHS,ISO9001:2015
Temperature range:-55°C~250°C	Temperature range:-40°C~105°C	Temperature range:-55°C~85°C
Various contact types:Straight solder and Print Elbow print 90°	Various contact types:Straight solder, Print and Elbow print 90°	Various contact types:Straight solder and Print and Elbow print 90°
360°screening for full EMC shielding	360°screening for full EMC shielding	360°screening for full EMC shielding
IP50	IP50	IP50
Cable diameter:1-7mm	Cable diameter:1-7mm	Cable diameter:1-11mm

Cable Assembly

