



UAC Series Waterproof Connector

UAC 系列防水连接器

一字防水连接器

"1" Type Waterproof Connector

使用时，将电缆两端分别穿过防水接头及主体外壳，将两端导线分别插入接线模块对应接口，并锁紧固定；剥线长度6-7mm。

First, put the both ends of the cables through the cable gland and main housing body during using, then insert them into the corresponding part of the wiring module and screw tightly. Stripper length: 6-7MM.



UAC-200/3 (三芯 3 Pins)

绝缘主体：尼龙阻燃
压线框：黄铜镀镍 Frame:Nickel plated brass
压线螺钉：钢 Screw:Steel
接线容量：Wire capacity: 0.5-4mm²
电压/电流：Voltage/Current:450V/25A
防护等级：Protect degree:IP68
电缆直径：Cable diameter:Φ 4~6mm

UAC-200/5 (五芯 5 Pins)

绝缘主体：Body:PA66
压线框：黄铜镀镍 Frame:Nickel plated brass
压线螺钉：钢 Screw:Steel
接线容量：Wire capacity: 0.5-2.5mm²
电压/电流：Voltage/Current:450V/25A
防护等级：Protect degree:IP68
电缆直径：Cable diameter:Φ 4~6mm



T形防水连接器

"T" Type Waterproof Connector

UAC防水连接器由电缆防水接头、主体外壳、接线模块三部分构成，具有电缆连接固定和防水密封双重作用，可广泛用于户外布线、煤矿、路灯照明、花园布线等潮湿环境。

UAC waterproof connector consists of cable gland, main housing body and wiring module. It has function both for cable connection and fixation or waterproof sealing. And can be widely used in outdoor wiring, coal mine, street lighting, garden wiring and other humid environment.



UAC-200/3T (三芯 3) Pins

绝缘主体：尼龙阻燃
压线框：黄铜镀镍 Frame:Nickel plated brass
压线螺钉：钢 Screw:Steel
接线容量：Wire capacity: 0.5-2.5mm²
电压/电流：Voltage/Current:450V/25A
防护等级：Protect degree:IP68
电缆直径：Cable diameter:Φ 4~6mm

UAC-200/5T (五芯 5 Pins)

绝缘主体 Body:PA66
压线框：黄铜镀镍 Frame:Nickel plated brass
压线螺钉：钢 Screw:Steel
接线容量：Wire capacity: 0.5-2.5mm²
电压/电流：Voltage/Current:450V/25A
防护等级：Protect degree:IP68
电缆直径：Cable diameter: Φ 4~6mm

