

	~		
	ſ ⊑	٦ĺ	
ы. М			

	Available Coding	A-coding			
M5 Quick Search Table	Rated Current	1A			
	Voltage	60V			
	Wire Gauge / size	26AWG / 0.14mm ²			
	Pin layout	(1) 3 • •4 Male	Female	2 • • 1 3 • • 4 Male	10 02 40 03 Female
M5 cables & conne	ctors		Pins		Pins
Molded Cable					
	Male Molded Cable Straight	04	-	04	-
	Male Molded Cable Straight Shield	06	-	06	-
and a start and a	Male Molded Cable Angled	08	-	08	-
	Female Molded Cable Straight	-	05	-	05
	Female Molded Cable Straight Shield	-	07	-	07
	Female Molded Cable Angled	-	09	-	09
Panel Mount Type					
	Male Panel Mount Solder Front Fastened	10	-	10	-
	Male Panel Mount Solder Rear Fastened	12	-	12	-
	Female Panel Mount Solder Front Fastened	-	11	-	11
👾 जन 👾 लि	Female Panel Mount Solder Rear Fastened	-	13	-	13
	Male Panel Mount PCB Type Front Fastened	14	-	14	-
	Male Panel Mount PCB Type Front Fastened Shield	16	-	16	-
	Female Panel Mount PCB Type Front Fastened	-	15	-	15
	Female Panel Mount PCB Type Front Fastened Shield	-	17	-	17

