


Features

- 5500 Watts peak pulse power ($t_p = 8/20\mu s$)
- DFN2020-3 package
- Unidirectional configurations
- Low clamping voltage
- Low leakage current
- Medium capacitance ($C_j=680pF$ typ.)
- Protection one data/power line to:
 - IEC 61000-4-2 $\pm 30kV$ contact $\pm 30kV$ air
 - IEC 61000-4-4 (EFT) 40A (5/50ns)
 - IEC 61000-4-5 (Lightning) 130A (8/20 μs)



Mechanical Data

- **Case:** DFN2020-3 (plastic package).
Lead free; RoHS compliant; Halogen free
- **Molding Compound Flammability Rating:**
UL 94 V-0
- **Terminals:** High temperature soldering guaranteed:
260 °C/10 sec. at terminals

Applications

- Power lines
- USB Vbus Industrial Electronics
- Industrial Electronics
- Microcontroller Input Protection
- Computer & Consumer Electronics
- Automotive and Telecommunication

Absolute Maximum Ratings

Ratings at 25 °C, ambient temperature unless otherwise specified


Parameter	Symbol	Value	Unit
Peak Pulse Power ($T_P=8/20\mu s$)	P_{PP}	5500	W
ESD contact/air discharge (IEC-61000-4-2)	V_{ESD}	30/30	kV
Peak Pulse Current ($t_p = 8/20\mu s$)	I_{PP}	130	A
Junction Temperature	T_J	-55 to +125	°C
Storage temperature	T_{STG}	-55 to +150	°C

Electrical Characteristics


($T_A = 25$ °C unless otherwise specified)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Reverse stand-off Voltage	V_{RWM}				24	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1mA$	25.0	27.5	29	V
Reverse Leakage Current	I_R	$V_R=24V$			1	μA
Clamping Voltage (IEC 61000-4-5)	V_C	$I_{PP}=50A$			30	V
Clamping Voltage (IEC 61000-4-5)	V_C	$I_{PP}=100A$			40	V
Clamping Voltage (IEC 61000-4-5)	V_C	$I_{PP}=130A$		43	45	V
Junction Capacitance	C_J	$V_R=0V, f=1MHz$		680		pF


Typical Characteristics ($T_{amb} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified)




Package Dimensions



PAD Dimensions



Package information



Ordering information

Order code	Marking	Package	Packaging option	Base quantity	Packaging specification
YED20F324130V	T24 003	DFN2020-3	Tape and reel	3000pcs / reel	EIA STD RS-481