


### Features

- 40Watts peak pulse power ( $T_P = 8/20\mu s$ )
- DFN1006-2 package
- Unidirectional configurations
- Low clamping voltage
- Low leakage current
- Ultra Low capacitance ( $C_j = 0.65pF$  typ.)
- Protection one data/power line to:
  - IEC 61000-4-2  $\pm 25kV$  contact  $\pm 25kV$  air
  - IEC 61000-4-4 (EFT) 40A (5/50ns)
  - IEC 61000-4-5 (Lightning) 3A (8/20 $\mu s$ )



### Mechanical Data

- **Case:** DFN1006-2 (plastic package).  
Lead free; RoHS compliant; Halogen free
- **Molding Compound Flammability Rating:**  
UL 94 V-0
- **Terminals:** High temperature soldering guaranteed:  
260 °C/10 sec. at terminals

### Applications

- Cell Phone Handsets and Accessories
- Personal Digital Assistants (PDA's)
- Microprocessor based equipment
- Notebooks, Desktops, and Servers
- Portable Instrumentation

### Absolute Maximum Ratings

Ratings at 25 °C, ambient temperature unless otherwise specified


Parameter	Symbol	Value	Unit
Peak Pulse Power ( $T_P = 8/20\mu s$ )	$P_{PP}$	40	W
ESD contact/air discharge (IEC-61000-4-2)	$V_{ESD}$	25/25	kV
Peak Pulse Current ( $T_P = 8/20\mu s$ )	$I_{PP}$	3	A
Junction Temperature	$T_J$	-55 to +125	°C
Storage temperature	$T_{STG}$	-55 to +150	°C

### Electrical Characteristics


( $T_A = 25$  °C unless otherwise specified)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Reverse stand-off Voltage	$V_{RWM}$				3.3	V
Reverse Breakdown Voltage	$V_{BR}$	$I_T = 1mA$	5.0			V
Reverse Leakage Current	$I_R$	$V_R = 3.3V, T = 25$ C		0.1	0.5	$\mu A$
Clamping Voltage (IEC 61000-4-5)	$V_C$	$I_{PP} = 3A, T_P = 8/20\mu s$		10		V
Junction Capacitance	$C_J$	$V_R = 0V, f = 1MHz$		0.65		pF


**Typical Characteristics** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$  unless otherwise specified)




**Package Dimensions**



### Pad Dimensions



### Tape and Reel Specification



### Marking



### Ordering information

Order code	Package	Packaging option	Base quantity	Packaging specification
YEUD1023R03AV	DFN1006-2	Tape and reel	10000pcs / reel	EIA STD RS-481