



·AC· MK254GAN (3)(HR)



Dia.219x87mm / 8.5inch
1000~370 CFM

Metal Impeller, Reverse Airflow

Model No	Rated Volt VAC	Voltage Range VAC	Freq Hz	Input Power Watt	Ref. Speed RPM	Max.Airflow CFM	m3/min	Max.Static Pressure Inch/H2O	mm	Noise Level db(A)	PQ
MK254GAN11-1**	115	100~120	50/60	95/105	2800/3200	830/1000	23.5/28.3	0.78/0.60	19.81/15.24	70	2/1
MK254GAN11-2**	115	100~120	50/60	55/65	2300/2200	660/620	18.7/17.6	0.33/0.27	8.38/6.86	63	4/3
MK254GAN11-3**	115	100~120	50/60	32/40	1400/1600	415/500	11.8/14.2	0.25/0.20	6.35/5.08	46	6/5
MK254GAN11-4**	115	100~120	50/60	24/33	1200/1100	420/370	11.9/10.5	0.18/0.14	4.57/3.56	34	8/7
MK254GAN11-1/2**	115	100~120	50/60	95/105	2800/3200	830/1000	23.5/28.3	0.78/0.60	19.81/15.24	70	2/1
Dual speed				55/65	2300/2200	660/620	18.7/17.6	0.33/0.27	8.38/6.86	63	4/3
MK254GAN11-3/4**	115	100~120	50/60	32/40	1600/1500	560/500	15.9/14.2	0.25/0.20	6.35/5.08	46	6/5
Dual speed				24/33	1200/1100	420/370	11.9/10.5	0.18/0.14	4.57/3.56	34	8/7
MK254GAN22-1**	230	200~240	50/60	95/105	2800/3200	830/1000	23.5/28.3	0.78/0.60	19.81/15.24	70	2/1
MK254GAN22-2**	230	200~240	50/60	55/65	2300/2200	660/620	18.7/17.6	0.33/0.27	8.38/6.86	63	4/3
MK254GAN22-3**	230	200~240	50/60	32/40	1400/1600	415/500	11.8/14.2	0.25/0.20	6.35/5.08	46	6/5
MK254GAN22-1/2**	230	200~240	50/60	95/105	2800/3200	830/1000	23.5/28.3	0.78/0.60	19.81/15.24	70	2/1
Dual speed				55/65	2300/2200	660/620	18.7/17.6	0.33/0.27	8.38/6.86	63	4/3
MK254GAN22-3/4**	230	200~240	50/60	32/40	1600/1500	560/500	15.9/14.2	0.25/0.20	6.35/5.08	46	6/5
Dual speed				24/33	1200/1100	420/370	11.9/10.5	0.18/0.14	4.57/3.56	34	8/7

- The stated airflow, air pressure, noise levels are measured with housing orifice dia.: impeller Φ +1~1.5mm, at distance: approx. height of impeller + motor frame. The optimal operating data can only be depended on the installation conditions.
- ** = "WB" for wire lead type Ball bearing, or "TB" for terminal type Ball bearing
- 100, 200, 240V or special voltages 12, 24, 28, 38, 42, 48, 380~440~480... 50/60Hz, & dual voltage version available on request.
- Dual speed High/Medium 1/2, High/Low 1/3, Medium/Low 2/3, Low/extra Low 3/4 or triple speed 1/2/3 available on request.
- Sinwan reserves the right to change data and improve electrical or mechanical design without notice, data tolerance $\pm$ 10%

Motor

Motor Type:	Capacitor Induction, Outer rotor, 2/4 pole, Single/3 phase (option)
Burnout Protection:	Thermal protected
IP Protection:	IP56

Mechanical

Frame:	Aluminum die cast, black cosmetics, Natural or any colors available
Impeller:	Steel-sheet metal fan blades, integrantly spot welded onto rotor
Bearing:	Two ball bearings
Rotation:	CCW seen on rotor
Connection:	Wire leads
Weight:	-


Electronical

Dielectric Strength:	Over 1 min.at 1,500 VAC
Insulation Resistance:	100Mega ohm min. at 500VDC
Signal Output:	-


Environment

Operating Temp:	-30~+80C
Storage Temp:	-40C~+100C
Life Expectancy:	L10 50K hours at 55C

Performance P-Q Curves



Outline Dimensions



Relevant products

UL **UL** **US** **CE** **RoHS**