DC AXIAL FAN

RUNDA
www.szrunda.com


180x180x60mm

RD 18060



外框材质:铝合金
Frame:Aluminum
扇叶材质:环保防火PC
Imperller:Thermoplastic PC UL94-V0
轴承结构:双滚珠
Bearing system:2Ball
单体风扇重量:1250g
Unit Weight:1250g

DIMENSIONS DRAWING



可选的功能参照列表
(Available Functions)

1.马达保护(Motor protection)


RP	SS	AS	CL
●	●	●	●


2.信号输出(Signal output)

FG	RD	RD	LD
●	●	●	●

3.调速方式(Speed control mode)

PWM	TP	VC	RC	CS
●	●	●	●	●





Part Number	Voltage(V)	Current(A)	Power(W)	Speed(RPM)	Air flow(Q)		Pressure(P)		Noise(dBA)
产品编号	电压范围	额定电流	功率	转速	(CFM)风量	m^3/min	(mmAq)风压	(In H_2O)	噪音
RD18060B12L	12(7~14)	2.36	28.32	2500	373.03	10.55	17.03	0.67	56.38
RD18060B12M		3.25	39.00	2800	379.73	10.74	21.36	0.84	59.82
RD18060B24L	24(15~27)	1.18	28.32	2500	373.03	10.55	17.03	0.67	56.38
RD18060B24M		1.63	39.12	2800	379.73	10.74	21.36	0.84	59.82
RD18060B24H		2.16	51.84	3200	433.98	12.28	27.90	1.10	62.95
RD18060B24VH		2.84	68.16	3500	474.67	13.43	33.38	1.31	66.53
RD18060B24SH		3.60	86.40	3800	515.35	14.58	39.34	1.55	68.80
RD18060B48L	48(35~57)	0.59	28.32	2500	373.03	10.55	17.03	0.67	56.38
RD18060B48M		0.82	39.36	2800	379.73	10.74	21.36	0.84	59.82
RD18060B48H		1.08	51.84	3200	433.98	12.28	27.90	1.10	62.95
RD18060B48VH		1.42	68.16	3500	474.67	13.43	33.38	1.31	66.53
RD18060B48SH		1.80	86.40	3800	515.35	14.58	39.34	1.55	68.80

★ 如果您需要的转速或电压或功能不在这份清单上，请与我们业务联系。
If you want another rpm or voltage or functions which one is not in the list,please contact with our sales.

★ 提示1:功能的具体信息参照产品目录前页篇章。
Notes1:The catalog have detail information in the front page for the functions.

★ 提示2:产品详细信息请参照承认书。
Notes2:Product have a detail in the approval sheet.

★ 提示3:产品规格变更不另行通知。
Notes3:Specifications are subject to change without notice.

★ 提示4:调速方式只能制作12V机型。
Note4:Speed control mode only for 12V products.

EL.ITALIA SRL
www.elitaliaweb.it
info@elitaliaweb.it
02.26261009
02.33611626