

Datasheet | EB02

EP-326-E Series



General Purpose AC EMI Filter

El.italia EC-EB02[EP-326-E] serie



Technical specifications

Operating voltage	120/250 VAC
Current rating	1A-10A
Frequency	50/60Hz
Voltage drop	1 Volt max.
High potential test voltage	P -> E 1500VAC P -> N 1414VDC (applicable excluding surge suppressor filter)
Insulation resistance	≥ 300 MΩ @ 500VDC (PN→E)
Operating temperature	40°C / -25°C +85°C

*Image shown is for illustrative purpose only

Features and benefits

- | All filters provide high attenuation performance.
- | All filters compliance to EN60939-3:2015 & EN60939-2:2005 standards.
- | Filter available in panel mounting provision.
- | Single stage.
- | High reliable.
- | CRCA metal can with nickel plating provides good aesthetic and corrosion protection.
- | Input connection through IEC 60320 C14 plug.
- | Output connection with fast-on or wire terminal
- | Filters available in medical version without capacitor to earth.
- | With surge suppressor filters also available.

Attenuation Type

Single Stage

Standard

Applications

- | Portable electrical and electronic equipment
- | Datacom equipment
- | Rack mounting equipment
- | Control Panel
- | Medical equipment
- | Consumer product
- | Medical equipment
- | Industrial application
- | Electrical automation equipment
- | Test and measurement equipment

Datasheet | EB02


EP-326-E Series




Mechanical details

El.italia EC-EB02[EP-326-E] serie

Fast-on terminal




Wire terminal




All dimensions in mm.

Electrical schematic for filter


General purpose -




Medical equipment application -



General purpose with surge suppressor -



Medical equipment application with surge suppressor -



Datasheet | EB02

EP-326-E Series



Filter attenuation graph


El.italia EC-EB02[EP-326-E] serie

C = Common mode (asymmetrical) ———


D = Differential mode (symmetrical) -----

For general purpose


For 1A




For 3A



For 6A



For 10A



Datasheet | EB02

EP-326-E Series



Product Selection Table -

El.italia EC-EB02[EP-326-E] serie

Sr. No	Elcom part codes (ordering code)	Rated Current rating (A) @40°C	Leakage current (mA) @250 VAC	Terminals (X)		Max. Peak current (8/20 μ sec 1 time) (KA)	Energy surge rating (10/1000 μ sec) (Joules)	Approx. weight (gm)	Attenuation
				Fast-on 	Wire 				
1	EF-1B001X01E-B02	1	< 0.5	B	G	----	----	60	Standard
2	EF-1B001X02E-B02	1	< 0.5	B	G	6.5	175	60	Standard
3	EF-1B001X03E-B02	1	< 0.003	B	G	----	----	60	Standard
4	EF-1B001X04E-B02	1	< 0.003	B	G	6.5	175	60	Standard
5	EF-1B003X01E-B02	3	< 0.5	B	G	----	----	60	Standard
6	EF-1B003X02E-B02	3	< 0.5	B	G	6.5	175	60	Standard
7	EF-1B003X03E-B02	3	< 0.003	B	G	----	----	60	Standard
8	EF-1B003X04E-B02	3	< 0.003	B	G	6.5	175	60	Standard
9	EF-1B006X01E-B02	6	< 0.5	B	G	----	----	60	Standard
10	EF-1B006X02E-B02	6	< 0.5	B	G	6.5	175	60	Standard
11	EF-1B006X03E-B02	6	< 0.003	B	G	----	----	60	Standard
12	EF-1B006X04E-B02	6	< 0.003	B	G	6.5	175	60	Standard
13	EF-1B010X01E-B02	10	< 0.5	B	G	----	----	60	Standard
14	EF-1B010X02E-B02	10	< 0.5	B	G	6.5	175	60	Standard
15	EF-1B010X03E-B02	10	< 0.003	B	G	----	----	60	Standard
16	EF-1B010X04E-B02	10	< 0.003	B	G	6.5	175	60	Standard

- To compile complete part number, replace the 'X' with required output connection terminal. (e.g. EF-1B001B01E-B02)

- Maximum leakage under usual AC operating conditions (acc. IEC 60939-3). Note: if the neutral line is interrupted, worst case leakage could reach twice this level.

- Customize products provided on request.

Connection Type

Current Rating (A)	Fast -on	Wire	Earthing
1, 3 & 6	6.3 X 0.8mm	18AWG	Fast-on/wire leads
		14AWG	

Datasheet | EB02

EP-326-E Series



El.italia EC-EB02[EP-326-E] serie



EF - 1B CCC X YY E - B02

