





IES: UNLESS OTHERWISE SPECIFIED.

1. material: Contacts--brass, T=0.4mm;
Insulator--Glass Filled PBT, 94-V0;
2. terminal finish: Tin plated;
3. removed burrs and sharp edge.
4. For MINI automotive blade Fuses.
6. Suitable rated current: 30A@500VAC.
7. Insertion and extraction force: 1Kg Min.
8. Dielectric Strength: Min.AC1000V.
9. Contact Resistance: Max 50m ω .
10. temperature rise: 50°Max.
11. Insulation Resistance At 500V DC: 100M ω

RoHS COMPLIANT		PROJ.		P/N:	UY-SL506A		El.italia srl Via IV Novembre 72, 20019 Settimo Milanese (MI), Italy info@elitaliaweb.it www.elitaliaweb.it www.contenitoriplastici.it	
SCALE:	FIT	TOLERANCE		TITLE:				
UNIT:	MM	LINEAR	ANGLE		PCB MOUNT FUSE HOLDER			
SIZE:	A4	X. ± 1	X. ° ± 5°			DONGGUAN TIANRUI ELECTRONICS CO.,LTD.		
REV:	A	.X ± 0.38	.X ° ± 2°					
DATE:		.XX ± 0.25	.XX ° ± 1°					
SHEET:	1/1	.XXX ± 0.10						