



FuseHolder Detail Specification


MODEL 型号: UY-SL559, UY-SL560

Spec. 规格


Holder / No. 560




Holes in PCB



PC Mount,
for TR5®/TE5® Fuses



"A"	code	height
3.0 mm		13
4.3 mm		10



Specifications

Packaging

1	bulk (1000 pcs.)
0	bulk (500 pcs.)

Order Number

Holder	No. 560 0000 13 1
Holder	No. 560 0000 10 0
Holder	No. 560 0000 10 1

Mounting

PC Board, 5.08 mm pin spacing

Materials

Holder: Thermoplastic, UL 94 V-0
Polyester PCT

Metal parts: Copper alloy; solderable tinned

Electrical Data (23 °C)

Rated Voltage: 250 V
Max. Current/Power: 6.3 A/1.6 W

Soldering Heat Resistance

max. 280 °C, 10 s (Wave)

Minimum Cross Section

Conducting path - 0.1 mm²

Unit Weight


0.4 g

RoHS


Holder / No. 559



Holes in PCB



PC Mount,
for TR5®/TE5® Fuses
leadfree



Packaging

000	bulk (1000 pcs.)
-----	------------------

Mounting

PC Board, 7.18 mm pin spacing

Materials

Holder: Black Thermoplastic, UL94 V-0
Polyamide PA 6.6

Metal parts: Copper alloy; solderable tinned

Electrical Data (23 °C)

Rated Voltage: 250 V
Max. Current/Power: 6.3 A/1.6 W

Solderability

max. 260 °C, 10 s (Wave)

Minimum Cross Section

Conducting path - 0.1 mm²

Unit Weight

0.63 g

RoHS

