




REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.6.02	ZHANG	JIN



• Material
 ①Screw : M1.6 steel, Zinc plated, "—" slot type
 ②Housing : PA66, UL94V-0
 ③Contact : Copper alloy, Tin plated
 ④Clamp : Copper alloy, Ni plated
 ⑤Cover : PA66, UL94V-0


• Electrical
 UL IEC
 Rated voltage : 150V 130V
 Rated current : 5A 10A
 Contact resistance : 20mΩ(Max)
 Insulation resistance : 500MΩ/DC500V
 Withstanding Voltage : AC1250V/1min
 Wire range : 24-20AWG 0.5mm²

• Mechanical
 Operating temperature: -40℃~+105℃
 Soldering temperature: 250℃±5/sec
 Torque : 0.1N.m (0.89Lb.in)
 Strip length: 8mm

• RoHS compliance

HOW TO ORDER

KF12EY-2.54-XXP-1 X-XXXX



Pitch range	Nominal dimension range	PROJECTION	TITLE
>0	>0	0.1/10	KF12EY-2.54-XXP-1X
≤6	≤6	≤	SHEET SIZE A4
≤15	≤15	±2	SERIES KF12EY

SCALE	CUSTOMER DRAWING
1:1	1 OF 1
DRAWING NO.	W10001482

DF

慈溪市凯峰电子有限公司
 CIXI KAIFENG ELECTRONICS CO.,LTD