



REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.6.02	ZHANG	JIN



P.C.B.LAYOUT

- Material
 ØHousing : PA66, UL94V-0
 ØPin header : Copper alloy, Tin plated
- Electrical
 UL IEC
 Rated voltage : 150V 130V
 Rated current : 5A 10A
 Contact resistance : 20mΩ(Max)
 Insulation resistance : 500MΩ/DC500V
 Withstanding Voltage : AC1250V/1min
- Mechanical
 Operating temperature: -40℃~+105℃
 Soldering temperature: 250℃±5/5sec
- RoHS compliance




HOW TO ORDER

KF12EZR-2.5-XXP-1 X-XXXX



Pitch range		Nominal dimension range				PROJECTION	TITLE				
>0	>6	>10	>0	>30	>60	>100	>150	6.1/10	UNIT	mm	KF12EZR-2.5-XXP-1X
~8	~10	~24	~30	~60	~100	~150	~150	<	SHEET SIZE	A4	SERIES KF12EZR
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2	DRAWING TYPE CUSTOMER DRAWING		
SCALE		1:1		SHEET		1 OF 1		慈溪市凯峰电子有限公司			
DRAWING NO.		W10001502						CIXI KAIFENG ELECTRONICS CO.,LTD			

REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.6.02	ZHANG	JIN



P.C.B.LAYOUT

- Material
 ○Housing : PA66, UL94V-0
 ○Pin header : Copper alloy, Tin plated
- Electrical
 UL IEC
 Rated voltage : 150V 130V
 Rated current : 5A 10A
 Contact resistance : 20mΩ(Max)
 Insulation resistance: 500MΩ/DC500V
 Withstanding Voltage : AC1250V/1min
- Mechanical
 Operating temperature: -40℃~+105℃
 Soldering temperature: 250℃±5/5sec
- RoHS compliance

HOW TO ORDER

KF12EZR-2.54-XXP-1 X-XXXX






Pitch range	Nominal dimension range	PROJECTION
>0	>0	0.1/10
6	60	<
±0.15(±0.20)	±0.30(±0.50)	±150
±0.30(±0.30)	±0.50(±0.70)	±1.00(±1.30)
		±2

UNIT	TITLE
mm	KF12EZR-2.54-XXP-1X
SHEET SIZE	SERIES
A4	KF12EZR

SCALE	CUSTOMER DRAWING
1:1	
DRAWING NO.	SHEET
W10001522	1 OF 1

DF 慈溪市凯峰电子有限公司
CIXI KAIFENG ELECTRONICS CO.,LTD


REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.6.02	ZHANG	JIN



- Material
 ØHousing : PA66, UL94V-0
 ØPin header : Copper alloy, Tin plated
 ØCover : PA66, UL94V-0
- Electrical
 UL IEC
 Rated voltage : 150V 130V
 Rated current : 5A 10A
 Contact resistance : 20mΩ(Max)
 Insulation resistance : 500MΩ/DC500V
 Withstanding Voltage : AC1250V/1min
- Mechanical
 Operating temperature: -40°C ~ +105°C
 Soldering temperature: 250°C ± 5/sec
- RoHS compliance

HOW TO ORDER

KF12EZRH-2.5-2*XXP-1 X-XXXX



P.C.B.LAYOUT

Pitch range		Nominal dimension range				PROJECTION	
>0	>6	>10	>0	>30	>60	>100	0.1/10
6	10	24	30	60	100	150	<
±0.15(±0.20)		±0.30	±0.50	±0.70	±1.00	±1.30	±2

UNIT	mm	TITLE
SHEET SIZE	A4	SERIES

KF12EZRH-2.5-2*XXP-1X



KF12EZRH

SCALE	CUSTOMER DRAWING
1:1	SHEET 1 OF 1
DRAWING NO.	W10001542





慈溪市凯峰电子有限公司
CIXI KAIFENG ELECTRONICS CO.,LTD

REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.6.02	ZHANG	JIN




0.8*0.8
3.9±0.3



- Material
 ○Housing : PA66, UL94V-0
 ○Pin header : Copper alloy, Tin plated
- Electrical
 UL IEC
 Rated voltage : 150V 130V
 Rated current : 5A 10A
 Contact resistance : 20mΩ(Max)
 Insulation resistance: 500MΩ/DC500V
 Withstanding Voltage : AC1250V/1min
- Mechanical
 Operating temperature: -40℃~+105℃
 Soldering temperature: 250℃±5/5sec
- RoHS compliance

HOW TO ORDER

KF12EZV-2.5-XXP-1 X-XXXXX



P.C.B.LAYOUT




Pitch range	Nominal dimension range	PROJECTION
>0 ~ >6 8 ~ 10	>0 ~ >30 30 ~ 60	0.1/10 ≤
>10 ~ >30 30 ~ 24	>60 ~ >100 100 ~ 150	≤
±0.15/±0.20 ±0.30/±0.30	±0.30/±0.50 ±0.70/±1.00	±1.30
		±2

UNIT	TITLE
mm	KF12EZV-2.5-XXP-1X
SHEET SIZE	SERIES
A4	KF12EZV


SCALE	CUSTOMER DRAWING
1:1	1 OF 1
DRAWING NO.	W10001492

DF 慈溪市凯峰电子有限公司
 CIXI KAIFENG ELECTRONICS CO.,LTD

REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.6.02	ZHANG	JIN



P.C.B.LAYOUT



- Material
 ØHousing : PA66, UL94V-0
 ØPin header : Copper alloy, Tin plated
- Electrical
 UL IEC
 Rated voltage : 150V 130V
 Rated current : 5A 10A
 Contact resistance : 20mΩ(Max)
 Insulation resistance: 500MΩ/DC500V
 Withstanding Voltage : AC1250V/1min
- Mechanical
 Operating temperature: -40℃~+105℃
 Soldering temperature: 250℃±5/5sec
- RoHS compliance




HOW TO ORDER

KF12EZV-2.54-XXP-1 X-XXXX



Pitch range	Nominal dimension range	PROJECTION	UNIT	TITLE
>0	>0	0.1/10	mm	KF12EZV-2.54-XXP-1X
≤0.1	≤0.1	<	A4	SERIES KF12EZV
CUSTOMER DRAWING		慈溪市凯峰电子有限公司 CIXI KAIFENG ELECTRONICS CO.,LTD		
SCALE	1:1 SHEET 1 OF 1			
DRAWING NO.	W10001512			

REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.6.02	ZHANG	JIN



P.C.B.LAYOUT

- Material
 - ①Housing : PA66, UL94V-0
 - ②Pin header : Copper alloy, Tin plated
 - ③Cover : PA66, UL94V-0
- Electrical
 - UL IEC
 - Rated voltage : 150V 130V
 - Rated current : 5A 10A
 - Contact resistance : 20mΩ(Max)
 - Insulation resistance: 500MΩ/DC500V
 - Withstanding Voltage : AC1250V/1min
- Mechanical
 - Operating temperature: -40℃~+105℃
 - Soldering temperature: 250℃±5/5sec
- RoHS compliance

HOW TO ORDER

KF12EZVH-2.5-2*XXP-1 X-XXXXX



Pitch range	Nominal dimension range	PROJECTION	TITLE
>0	>6	6.1/10	KF12EZVH-2.5-2*XXP-1X
>10	>30	<	SHEET SIZE A4
>6	>10		SERIES KF12EZVH
±0.15/±0.20	±0.30/±0.50		
±0.70/±1.00	±1.30		
±2			
DRAWING TYPE CUSTOMER DRAWING		慈溪市凯峰电子有限公司 CIXI KAIFENG ELECTRONICS CO.,LTD	
SCALE	1:1 SHEET 1 OF 1		
DRAWING NO.	W10001532		