






REV	DESCRIPTION	DATE	DRAWN	APPROVED
A1	DWG.REL	2016/10/	FANG	YANG



N=Number of Poles
 Dim P=(N-1)×5.00
 Dim L=N×5.00

Poles	Dim	Dim P	Dim L
2-6P	±0.10	±0.15	
7-12P	±0.20	±0.20	
13-18P	±0.25	±0.30	
19-24P	±0.30	±0.40	


- Material
 - ⊙Screws : M2.5 steel, Zinc plated, - slot type
 - ⊙Housing : PA66, UL94V-0
 - ⊙Reed : Phosphor bronze, Ni plated or stainless steel
 - ⊙Pin header : Brass, Tin plated

- Electrical
 - UL IEC
 - Rated voltage : 300V 250V
 - Rated current : 16A 22A
 - Insulation resistance: 500MΩ/DC500V
 - Withstanding Voltage : AC200V/1min
 - Wire range: 22-14AWG 2.5mm²

- Mechanical
 - Operating temperature: -40℃~+105℃
 - Soldering temperature: 250℃±5/5sec
 - Torque: 0.4N.m (3.54Lb.in)
 - Strip length: 6-7mm

HOW TO ORDER

KF166-5.0-XXP-1 X-XXXX



GENERAL TOLERANCE ANGLE TOLERANCE

X.	±0.5	X'.	±5'
.X	±0.3	.X'	±3'
.XX	±0.1	.XX'	±1'

PROJECTION TITLE KF166-5.0-XXP

UNITS mm

SHEET SIZE A4 SERIES KF166

DRAWING TYPE CUSTOMER

SCALE 1:1 SHEET 1 OF 1

DRAWING NO. XPO012016-XXXX

DF 慈溪市凯峰电子有限公司
 KAIFENG ELECTRONIC CIXI KAIFENG ELECTRONIC CO.LTD