



REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.05.22	DENG	JIN




• Material
 ØScrews : M2.5 steel, Zinc plated,
 - slot type
 ØHousing : PA66, UL94V-0
 ØClamp : Copper alloy, Ni plated
 ØPin header : Copper alloy, Tin plated

• Electrical
 UL IEC
 Rated voltage : 300V 250V
 Rated current : 15A 22A
 Contact Resistance: 20mΩ
 Insulation resistance: 500MΩ/DC500V
 Withstanding Voltage : AC2000V/1min
 Wire range: 22-14AWG 0.5-2.5mm²

• Mechanical
 Operating temperature: -40°C~+105°C
 Soldering temperature: 250°C±5/5sec
 Torque: 0.4N.m (3.54Lb.in)
 Strip length: 5-6mm

• RoHS compliance

HOW TO ORDER



P.C.B.LAYOUT

Pitch range	Nominal dimension range	PROJECTION	UNIT	TITLE
>0	>0	0.1/10	mm	KF169-5.0-XXP-1X
6	60	<	SHEET SIZE	A4
DRAWING TYPE		CUSTOMER DRAWING		
SCALE		1:1 SHEET 1 OF 1		
DRAWING NO.		W15000772		

DF

慈溪市凯峰电子有限公司
 CIXI KAIFENG ELECTRONICS CO.,LTD