





REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.6.02	ZHANG	JIN




P.C.B. LAYOUT

- Material
  - ⊙Housing : PA66, UL94V-0
  - ⊙Pin header : Copper alloy, Tin plated
- Electrical
  - UL IEC
  - Rated voltage : 300V 320V
  - Rated current : 15A 20A
  - Contact resistance : 20mΩ(Max)
  - Insulation resistance: 500MΩ/DC500V
  - Withstanding Voltage : AC2000V/1min
- Mechanical
  - Operating temperature: -40℃~+105℃
  - Soldering temperature: 250℃±5/5sec
- RoHS compliance

HOW TO ORDER

KF2EDGCR-X-5.0-XXP-1 X-XXXXX






Pitch range	Nominal dimension range	PROJECTION	UNIT	TITLE					
>0	>6	>10	>30	>60	>100	>150	0.1/10	mm	KF2EDGCR-X-5.0-XXP-1X
0.8	1.0	2.4	3.0	6.0	10.0	15.0	<	A4	KF2EDGCR-X
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2	
DRAWING NO.		W10000682							

SCALE TYPE	CUSTOMER DRAWING
1:1	SHEET 1 OF 1



慈溪市凯峰电子有限公司  
CIXI KAIFENG ELECTRONICS CO.,LTD

REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.6.02	ZHANG	JIN



P.C.B.LAYOUT

- Material
  - ⊙Housing : PA66, UL94V-0
  - ⊙Pin header : Copper alloy, Tin plated
- Electrical
  - UL IEC
  - Rated voltage : 300V 320V
  - Rated current : 15A 20A
  - Contact resistance : 20mΩ(Max)
  - Insulation resistance : 500MΩ/DC500V
  - Withstanding Voltage : AC2000V/1min
- Mechanical
  - Operating temperature: -40°C ~ +105°C
  - Soldering temperature: 250°C ± 5/5sec
- RoHS compliance

HOW TO ORDER

KF2EDGCR-X-5.08-XXP-1 X-XXXX



Pitch range		Nominal dimension range				PROJECTION	TITLE
>0	>6	>10	>0	>30	>60	>100	6.1/10
6	10	24	30	60	100	150	<
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±2
DRAWING TYPE		CUSTOMER DRAWING					
SCALE		1:1 SHEET 1 OF 1					
DRAWING NO.		W10000632					



UNIT

mm

TITLE KF2EDGCR-X-5.08-XXP-1X



SHEET SIZE

A4

SERIES



KF2EDGCR-X



慈溪市凯峰电子有限公司

CIXI KAIFENG ELECTRONICS CO.,LTD

REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.5.18	ZHANG	JIN




P.C.B.LAYOUT

- Material
  - ⊙Housing : PA66, UL94V-0
  - ⊙Pin header : Copper alloy, Tin plated
- Electrical
  - UL IEC
  - Rated voltage : 300V 400V
  - Rated current : 15A 20A
  - Contact resistance : 20mΩ(Max)
  - Insulation resistance : 500MΩ/DC500V
  - Withstanding Voltage : AC2500V/1min
- Mechanical
  - Operating temperature : -40℃~+105℃
  - Soldering temperature : 250℃±5/5sec
- RoHS compliance

#### HOW TO ORDER

**KF2EDGCR-X-7.5-XXP-1 X-XXXXX**







Pitch range		Nominal dimension range				PROJECTION	TITLE
>0	>6	>10	>0	>30	>60	>100	6.1/10
6	10	24	30	60	100	150	<
±0.15(±0.20)		±0.30	±0.30	±0.50	±0.70	±1.00	±2
DRAWING TYPE		CUSTOMER DRAWING					
SCALE		1:1		SHEET		1 OF 1	
DRAWING NO.		W10000112					
UNIT							mm
SHEET SIZE							A4
SERIES							KF2EDGCR-X
TITLE							KF2EDGCR-X-7.5-XXP-1X



慈溪市凯峰电子有限公司  
CIXI KAIFENG ELECTRONICS CO.,LTD

REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.5.20	ZHANG	JIN



P.C.B.LAYOUT

- Material  
 ○Housing : PA66, UL94V-0  
 ○Pin header : Copper alloy, Tin plated
- Electrical IEC  
 Rated voltage : 300V 400V  
 Rated current : 15A 20A  
 Contact resistance : 20mΩ(Max)  
 Insulation resistance : 500MΩ/DC500V  
 Withstanding Voltage : AC2500V/1min
- Mechanical  
 Operating temperature : -40°C ~ +105°C  
 Soldering temperature : 250°C ± 5/5sec
- RoHS compliance

HOW TO ORDER

KF2EDGCR-X-7.62-XXP-1 X-XXXX







Pitch range		Nominal dimension range				PROJECTION	UNIT	TITLE
>0	>6	>10	>0	>30	>60	>100	6.1/10	KF2EDGCR-X-7.62-XXP-1X
6	10	24	30	60	100	150	≤	SHEET SIZE A4
±0.15/±0.20/±0.30		±0.30/±0.50/±0.70/±1.00/±1.30		±2		SERIES KF2EDGCR-X		
DRAWING TYPE		CUSTOMER DRAWING						
SCALE		1:1 SHEET 1 OF 1						
DRAWING NO.		W10000192						



慈溪市凯峰电子有限公司  
CIXI KAIFENG ELECTRONICS CO., LTD

REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.6.02	ZHANG	JIN



P.C.B. LAYOUT

- Material
  - ⊙Housing : PA66, UL94V-0
  - ⊙Pin header : Copper alloy, Tin plated
- Electrical
  - UL IEC
  - Rated voltage : 300V 320V
  - Rated current : 15A 20A
  - Contact resistance : 20mΩ(Max)
  - Insulation resistance: 500MΩ/DC500V
  - Withstanding Voltage : AC2000V/1min
- Mechanical
  - Operating temperature: -40℃ ~ +105℃
  - Soldering temperature: 250℃ ± 5/5sec
- RoHS compliance

HOW TO ORDER

KF2EDGCV-X-5.0-XXP-1 X-XXXXX








Pitch range	Nominal dimension range	PROJECTION
>0	>6	0.1/10
>10	>30	<
6	10	
24	30	
30	60	
60	100	
100	150	
150	2150	
±0.15(±0.20)	±0.30(±0.50)	±1.00(±1.30)
±0.30(±0.50)	±0.70(±1.00)	±1.30(±2)

UNIT	TITLE
mm	KF2EDGCV-X-5.0-XXP-1X
SHEET SIZE	SERIES
A4	KF2EDGCV-X

DRAWING TYPE	CUSTOMER DRAWING
SCALE	1:1 SHEET 1 OF 1
DRAWING NO.	W10000672

**DF** 慈溪市凯峰电子有限公司  
CIXI KAIFENG ELECTRONICS CO.,LTD

REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.6.02	ZHANG	JIN




P.C.B.LAYOUT

- Material
  - ⊙Housing : PA66, UL94V-0
  - ⊙Pin header : Copper alloy, Tin plated
- Electrical
  - UL IEC
  - Rated voltage : 300V 320V
  - Rated current : 15A 20A
  - Contact resistance : 20mΩ(Max)
  - Insulation resistance : 500MΩ/DC500V
  - Withstanding Voltage : AC2000V/1min
- Mechanical
  - Operating temperature: -40°C ~ +105°C
  - Soldering temperature: 250°C ± 5/5sec
- RoHS compliance

HOW TO ORDER

KF2EDGCV-X-5.08-XXP-1 X-XXXX






Pitch range		Nominal dimension range				PROJECTION	UNIT	TITLE
>0	>6	>10	>0	>30	>60	>100	0.1/10	KF2EDGCV-X-5.08-XXP-1X
6	10	24	30	60	100	150	<	SHEET SIZE A4
±0.15(±0.20)		±0.30	±0.50	±0.70	±1.00	±1.30	±2	SERIES KF2EDGCV-X

DRAWING TYPE		CUSTOMER DRAWING	
SCALE	1:1	SHEET	1 OF 1
DRAWING NO.	W10000622		



慈溪市凯峰电子有限公司  
CIXI KAIFENG ELECTRONICS CO.,LTD

REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.5.18	ZHANG	JIN




P.C.B. LAYOUT

- Material  
 ○Housing : PA66, UL94V-0  
 ○Pin header : Copper alloy, Tin plated
- Electrical  
 UL IEC  
 Rated voltage : 300V 400V  
 Rated current : 15A 20A  
 Contact resistance : 20mΩ(Max)  
 Insulation resistance: 500MΩ/DC500V  
 Withstanding Voltage : AC2500V/1min
- Mechanical  
 Operating temperature: -40℃~+105℃  
 Soldering temperature: 250℃±5/5sec
- RoHS compliance






HOW TO ORDER

KF2EDGCV-X-7.5-XXP-1 X-XXXX



Pitch range	Nominal dimension range	PROJECTION	TITLE
>0	>0	6.1/10	KF2EDGCV-X-7.5-XXP-1X
>6	>30	UNIT	mm
>10	>60	SHEET SIZE	A4
>24	>100	SERIES	KF2EDGCV-X
>30	>150	慈溪市凯峰电子有限公司 CIXI KAIFENG ELECTRONICS CO.,LTD	
>60	>150		
>100	>150	SCALE 1:1 SHEET 1 OF 1	
>150	>150	DRAWING NO. W10000102	

REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.5.20	ZHANG	JIN




P.C.B. LAYOUT

- Material  
 ⌀Housing : PA66, UL94V-0  
 ⌀Pin header : Copper alloy, Tin plated
- Electrical  
 UL IEC  
 Rated voltage : 300V 400V  
 Rated current : 15A 20A  
 Contact resistance : 20mΩ(Max)  
 Insulation resistance: 500MΩ/DC500V  
 Withstanding Voltage : AC2500V/1min
- Mechanical  
 Operating temperature: -40℃~+105℃  
 Soldering temperature: 250℃±5/5sec
- RoHS compliance

HOW TO ORDER

KF2EDGCV-X-7.62-XXP-1 X-XXXXX



Pitch range	Nominal dimension range	PROJECTION
>0	>0	6.1/10
>6	>30	<
8	10 24 30	
±0.15	±0.20 ±0.30 ±0.30 ±0.50 ±0.70 ±1.00 ±1.30 ±2	

UNIT	TITLE
mm	KF2EDGCV-X-7.62-XXP-1X
SHEET SIZE	SERIES
A4	KF2EDGCV-X

DRAWING TYPE	CUSTOMER DRAWING
SCALE	1:1 SHEET 1 OF 1
DRAWING NO.	W10000182

**DF** 慈溪市凯峰电子有限公司  
CIXI KAIFENG ELECTRONICS CO.,LTD