

P.C.B. LAYOUT

REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.5.20	ZHANG	JIN

- Material
 - ØHousing : PA66, UL94V-0
 - ØPin header : Copper alloy, Ag plated
- Electrical
 - UL IEC
 - Rated voltage : 300V 320V
 - Rated current : 15A 20A
 - Contact resistance : 20mΩ(Max)
 - Insulation resistance : 500MΩ/DC500V
 - Withstanding Voltage : AC2000V/1min
- Mechanical
 - Operating temperature: -40°C ~ +105°C
 - Soldering temperature: 250°C ±5/5sec
- RoHS compliance

HOW TO ORDER

KF2EFV-5.0-XXP-1 X-XXXX








Pitch range	Nominal dimension range	PROJECTION
>0	>6	0.1/10
>10	>30	<
6	10	
24	30	
30	60	
60	100	
100	150	
150	150	
±0.15	±0.20	±0.30
±0.30	±0.30	±0.50
±0.50	±0.70	±1.00
±1.00	±1.30	±2

UNIT	TITLE
mm	KF2EFV-5.0-XXP-1X
SHEET SIZE	SERIES
A4	KF2EFV

DRAWING NO.	SCALE	CUSTOMER DRAWING
W10001882	1:1	SHEET 1 OF 1

DF 慈溪市凯峰电子有限公司
CIXI KAIFENG ELECTRONICS CO., LTD



P.C.B. LAYOUT

REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.5.20	ZHANG	JIN

- Material
 - ØHousing : PA66, UL94V-0
 - ØPin header : Copper alloy, Ag plated
- Electrical
 - UL IEC
 - Rated voltage : 300V 320V
 - Rated current : 15A 20A
 - Contact resistance : 20mΩ(Max)
 - Insulation resistance : 500MΩ/DC500V
 - Withstanding Voltage : AC2000V/1min
- Mechanical
 - Operating temperature: -40°C ~ +105°C
 - Soldering temperature: 250°C ±5/5sec
- RoHS compliance

HOW TO ORDER

KF2EFV-5.08-XXP-1 X-XXXX







Pitch range	Nominal dimension range	PROJECTION
>0	>6	0.1/10
>10	>30	<
6	10	
24	30	
30	60	
60	100	
100	150	
150	150	
±0.15	±0.20	±2
±0.30	±0.30	
±0.50	±0.70	
±1.00	±1.30	
±1.30	±2	

UNIT	TITLE
mm	KF2EFV-5.08-XXP-1X
SHEET SIZE	SERIES
A4	KF2EFV

DRAWING NO.	CUSTOMER DRAWING
W10001842	1:1 SHEET 1 OF 1

DF 慈溪市凯峰电子有限公司
CIXI KAIFENG ELECTRONICS CO., LTD

REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.5.20	ZHANG	JIN



P.C.B.LAYOUT

Pitch range		Nominal dimension range				PROJECTION	UNIT	TITLE
>0	>6	>10	>0	>30	>60	>100	0.1/10	KF2EFVM-5.0-XXP-1X
6	10	24	30	60	100	150	<	SHEET SIZE A4
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±2	SERIES KF2EFVM
DRAWING TYPE		CUSTOMER DRAWING						
SCALE		1:1 SHEET 1 OF 1						
DRAWING NO.		W10001902						

- Material
 - ØHousing : PA66, UL94V-0
 - ØPin header : Copper alloy, Ag plated
 - ØNut : M2.5, Brass

- Electrical
 - UL IEC
 - Rated voltage : 300V 320V
 - Rated current : 15A 20A
 - Contact resistance : 20mΩ(Max)
 - Insulation resistance : 500MΩ/DC500V
 - Withstanding Voltage : AC2000V/1min

- Mechanical
 - Operating temperature : -40℃~+105℃
 - Soldering temperature : 250℃ ± 5/5sec

- RoHS compliance





HOW TO ORDER

KF2EFVM-5.0-XXP-1 X-XXXXX



慈溪市凯峰电子有限公司
CIXI KAIFENG ELECTRONICS CO., LTD

REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
A1	DWG.REL	2020.5.20	ZHANG	JIN



P.C.B.LAYOUT

Pitch range		Nominal dimension range				PROJECTION	UNIT	TITLE
>0	>6	>10	>0	>30	>60	>100	6.1/10	KF2EFVM-5.08-XXP-1X
6	10	24	30	60	100	150	<	SHEET SIZE A4
±0.15/±0.20		±0.30	±0.50	±0.70	±1.00	±1.30	±2	SERIES KF2EFVM
DRAWING TYPE		CUSTOMER DRAWING						
SCALE		1:1 SHEET 1 OF 1						
DRAWING NO.		W10001862						

- Material
 - ØHousing : PA66, UL94V-0
 - ØPin header : Copper alloy, Ag plated
 - ØNut : M2.5, Brass
- Electrical
 - UL IEC
 - Rated voltage : 300V 320V
 - Rated current : 15A 20A
 - Contact resistance : 20mΩ(Max)
 - Insulation resistance : 500MΩ/DC500V
 - Withstanding Voltage : AC2000V/1min
- Mechanical
 - Operating temperature : -40℃~+105℃
 - Soldering temperature : 250℃±5/5sec
- RoHS compliance

HOW TO ORDER

KF2EFVM-5.08-XXP-1 X-XXXXX



慈溪市凯峰电子有限公司
CIXI KAIFENG ELECTRONICS CO., LTD