


M12 Multi-Way 4T-Splitter, Male-3*Female

- Connector series: M12
- Gender: Male&Female
- Coding: A,B,D
- Locking type: Fix screw
- Mounting type: T type
- Part No.: M4T-*XX

* refers to coding type
XX refers to pins number



General information



Standard:	IEC 61076-2-101
Ambient temperature:	-20°C ~ + 80°C
Connector insert:	TPU; PA
Connector contacts:	Brass with gold plated
Connector nut/screw:	Zinc alloy with nickel plated
Connector overmold:	TPU
Seal/O-ring:	FKM

Insulation resistance:	≥ 100MΩ
Contact resistance :	≤ 5mΩ
Shielding:	Unavailable
IP rating:	IP68 in locked condition
Mating endurance:	>500 cycles

Electrical data & Mechanical data

Contacts	Available Coding			Rated current	Voltage		Part No.
	A	B	D		A/C	D/C	
03 pins	 Male Female	 Male Female		4A	250V	250V	M4T-A03 M4T-B03
04 pins	 Male Female	 Male Female	 Male Female	4A	250V	250V	M4T-A04 M4T-B04 M4T-D04
05 pins	 Male Female	 Male Female		4A	60V	60V	M4T-A05 M4T-B05
08 pins	 Male Female			2A	30V	30V	M4T-A08