


M12 Female Molded Cable, Angled, Plastic Nut

- Connector series: M12
- Gender: Female
- Coding: A,B,C,D
- Locking type: Plastic fix screw
- Mounting type: Right angled
- Part No.: MA12F*P**RAXXXXXX

* refers to coding type

** refers to pins number

X refers to cable specification



General information



Standard:	IEC 61076-2-101
Ambient temperature:	-40°C ~ +80°C(fixed installation) -20°C ~ +80°C(flexible installation)
Connector insert:	TPU; PA
Connector overmold:	TPU
Coupling nut/screw:	PA+GF
Seal / O-ring:	FKM

Connector contacts:	Brass with gold plated
Insulation resistance:	≥ 100MΩ
Contact resistance :	≤ 5mΩ
Shielding:	Unavailable
IP rating:	IP68, IP69K in locked condition
Mating endurance:	>500 cycles

Electrical data & Mechanical data

Contacts	Available Coding				Rated current	Voltage		Wire gauge / size		Cable jacket	Part No.
	A	B	C	D		A/C	D/C	AWG	mm ²		
03 pins					4A	250V	250V	22AWG	0.34	PUR / PVC	MA12FAP03RAXXXB34 MA12FBP03RAXXXB34 MA12FCP03RAXXXB34
04 pins					4A	250V	250V	22AWG	0.34	PUR / PVC	MA12FAP04RAXXXB34 MA12FBP04RAXXXB34 MA12FCP04RAXXXB34 MA12FDP04RAXXXB34
05 pins					4A 2A (C-code)	60V	60V	22AWG 24AWG (C-code)	0.34 0.25 (C-code)	PUR / PVC	MA12FAP05RAXXXB34 MA12FBP05RAXXXB34 MA12FCP05RAXXXB25
06 pins					2A	30V	30V	24AWG	0.25	PUR / PVC	MA12FCP06RAXXXB25
08 pins					2A	30V	30V	24AWG	0.25	PUR / PVC	MA12FAP08RAXXXB25
12 pins					1.5A	30V	30V	26AWG	0.14	PUR / PVC	MA12FAP12RAXXXB14
17 pins					1.5A	30V	30V	26AWG	0.14	PUR / PVC	MA12FAP17RAXXXB14

*12pin, 17pin with different overmold from above other pins.

Note: X refers to cable specification

Remarks

- Please refer to Page 578 for the Conversion between American Wire Gauge AWG and Wire Cross-section mm².
- Please refer to Page 96 for products' part number encoding rule.