


M12 Male Molded Cable, Straight, Y3-coding, Shielded

- Connector series: M12
 - Gender: Male
 - Coding: Y3
 - Locking type: Fix screw
 - Mounting type: Straight
 - Part No.: MA12MSY3F06STXXXXXX
- X refers to cable specification



General information



Standard:	IEC 61076-2-113
Ambient temperature:	-40°C ~ +80°C(fixed installation) -20°C ~ +80°C(flexible installation)
Connector insert:	TPU+GF
Connector contacts:	Brass with gold plated
Connector overmold:	TPU
Connector nut/screw:	Brass with nickel plated
Seal / O-ring:	FKM

Insulation resistance:	≥ 100MΩ
Contact resistance :	≤ 10mΩ
Shielding:	Available
IP rating:	IP67 in locked condition
Mating endurance:	>500 cycles

Electrical data & Mechanical data

Contacts	Rated current	Voltage		Wire gauge / size		Cable jacket	Wire insulation	Part No.
		A/C	D/C	AWG	mm ²			
06 pins	12A (Power pins) 0.5A (Signal pins)	50V	50V	16AWG (Power pins) 26AWG (Signal pins)	1.25 (Power pins) 0.15 (Signal pins)	PUR / PVC	PE+PP	MA12MSY3F06STXXXXXX

Note: X refers to cable specification

Remarks

- Please refer to Page 578 for the Conversion between American Wire Gauge AWG and Wire Cross-section mm².
- Please refer to Page 96 for products' part number encoding rule.