




## M12 Female Panel Mount, Plastic Screw/Nut, PCB Type, Front fastened

- Connector series: M12
- Gender: Female
- Coding: A,B,C,D
- Locking type: Plastic fix screw
- Mounting type: Front fastened
- Part No.: MB12FB\*FP\*\*ST-1
  - \* refers to coding type
  - \*\* refers to pins number









## ■ General information

Standard:	IEC 61076-2-101
Ambient temperature:	-25℃ ~ +90℃
Connector insert:	PA
Connector contacts:	Brass with gold plated
Connector nut/screw:	PA+GF
Seal / O-ring:	Epoxy resin / FKM

≥100MΩ
≤5mΩ
Unavailable
IP68 in locked condition
Refer to page 287
Refer to page 286
>500 cycles

## ■ Electrical data & Mechanical data

Contacts	Available Coding			Contacts	Rated	Voltage		Part No.	
	Α	В	С	D	termination	termination current	A/C	D/C	Part NO.
03 pins	30 04 01	30 04 01	оре 30 о2 (2+РЕ)		PCB version	4A	250V	250V	MB12FBAFP03ST-1 MB12FBBFP03ST-1 MB12FBCFP03ST-1
04 pins	30 04 20 01	30 04 20 01	(3+PE)	30 0 <sup>4</sup>	PCB version	4A	250V	250V	MB12FBAFP04ST-1 MB12FBBFP04ST-1 MB12FBCFP04ST-1 MB12FBDFP04ST-1
05 pins	30 04 05 20 01	30 04 05 20 01	20 04 10 05 (4+PE)		PCB version	4A 2A(C-code)	60V	60V	MB12FBAFP05ST-1 MB12FBBFP05ST-1 MB12FBCFP05ST-1
06 pins			PE 20 0 04 10 05 (5+PE)		PCB version	2A	30V	30V	MB12FBCFP06ST-1
08 pins	40 5 06 30 0 07 20 8 01				PCB version	2A	30V	30V	MB12FBAFP08ST-1

## ■ Remarks

• Please refer to Page 96 for products' part number encoding rule.

