


M12 Female Panel Mount, Crimp, Front fastened, T-coding

- Connector series: M12
- Gender: Female
- Coding: T
- Locking type: Fix screw
- Mounting type: Front fastened
- Part No.: MB12FCTFF**ST-XXXX

** refers to pins number
X refers to Chasis-side thread size
 XXX refers to cable specification



General information



Ambient temperature:	-20°C ~ +80°C
Connector insert:	PA
Connector contacts:	Brass with gold plated
Connector screw/nut:	Brass with nickel plated
Seal / O-ring:	Epoxy resin / FKM

Insulation resistance:	≥ 100MΩ
Contact resistance :	≤ 5mΩ
Shielding:	Unavailable
IP rating:	IP68 in locked condition
Panel cut-out:	Refer to page 287
Mating endurance:	>500 cycles

Electrical data & Mechanical data

Contacts	Contacts termination	Rated current	Rated voltage	Wire gauge / size		Wire insulation	Part No.
				AWG	mm ²		
04 pins 	Crimp version	12A(40°C)	60V	16AWG	1.5	PVC wire or customized	MB12FCTFF04ST- <u>X</u> 150

Note: X refers to Chasis-side thread size

Remarks

- Please refer to Page 578 for the Conversion between American Wire Gauge AWG and Wire Cross-section mm².
- Please refer to Page 96 for products' part number encoding rule.