


M12 Male Panel Mount, Plastic Screw, Solder, Rear fastened

- Connector series: M12
- Gender: Male
- Coding: A
- Locking type: Plastic fix screw
- Mounting type: Rear fastened
- Part No.: MB12MSARP**ST-2

** refers to pins number



General information

Standard:	IEC 61076-2-101
Ambient temperature:	-25°C ~ +90°C
Connector body:	PA+ GF
Connector contacts:	Brass with gold plated
Connector nut/screw:	PA+GF

Insulation resistance:	≥ 100MΩ
Contact resistance :	≤ 5mΩ
Shielding:	Unavailable
IP rating:	IP68 in locked condition
Panel cut-out:	Refer to page 287
Mating endurance:	>500 cycles

Electrical data & Mechanical data

Contacts	Contacts termination	Rated current	Voltage		Wire gauge / size		Wire insulation	Part No.	
			A/C	D/C	AWG	mm ²			
04 pins		Solder version	4A	250V	250V	22AWG	0.34	PVC wire or customized	MB12MSARP04ST-2
05 pins		Solder version	4A	60V	60V	22AWG	0.34	PVC wire or customized	MB12MSARP05ST-2
08 pins		Solder version	2A	30V	30V	24AWG	0.25	PVC wire or customized	MB12MSARP08ST-2

Remarks

- Please refer to Page 578 for the Conversion between American Wire Gauge AWG and Wire Cross-section mm².
- Please refer to Page 96 for products' part number encoding rule.