



M12 Plastic I-Adapter, Male-Female

• Connector series: M12

• Gender: Male&Female


• Coding: A,B,D


• Locking type: Plastic fix screw

• Mounting type: I type

• Part No.: MIP-*XX

* refers to coding type XX refers to pins number











■ General information

Standard:	IEC 61076-2-101
Ambient temperature:	-20℃~ + 80℃
Connector insert:	TPU; PA
Connector contacts:	Brass with gold plated
Connector nut/screw:	PA+GF
Connector overmold:	TPU
Seal/O-ring:	FKM

Insulation resistance:	≥100MΩ
Contact resistance :	≤5mΩ
Shielding:	Unavailable
IP rating:	IP68 in locked condition
Mating endurance:	>500 cycles

■ Electrical data & Mechanical data

Contacts -	Available Coding			Rated	Voltage		Part No.
	А	В	D	current	A/C	D/C	Part NO.
03 pins	(30 04) (18 01) Male Female	(4 ● ⊛3) (30 O4) (1 ● Male Female		4A	250V	250V	MIP-A03 MIP-B03
04 pins	(4) (3) (30 O4) (20 O1) Male Female	(40 03) (30 04) (30 01) Male Female	4	4A	250V	250V	MIP-A04 MIP-B04 MIP-D04
05 pins	(4) (8) (3) (3) (04) (2) (1) (1) (1) (1) (1) (1) (1) (1) (1) (1	(40 03) (30 04) 05 (20 01) Male Female		4A	60V	60V	MIP-A05 MIP-B05
08 pins	(60 5 04) (80 0 0 0) (10 8 0) (10 0 0 0 0 0 0 0 0 0) (10 0 0 0 0 0 0 0 0 0) (10 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0			2A	30V	30V	MIP-A08

