



M5 Female Molded Cable, Straight

• Connector series: M5

• Gender: Female


• Coding: A

• Locking type: Fix screw

• Mounting type: Straight

• Part No.: MA05FAF**STXXXX14

**refers to pins number X refers to cable specification









■ General information

IEC 61076-2-105				
-40 °C ~ $+80$ °C (fixed installation)				
-20°C ~ +80°C(flexible installation)				
TPU				
Brass with gold plated				
TPU				
Brass with nickel plated				
FKM				

Insulation resistance:	≥100MΩ
Contact resistance:	≤5mΩ
Shielding:	Unavailable
IP rating:	IP67 in locked condition
Mating endurance:	>500 cycles

■ Electrical data & Mechanical data

Cou		Contacts Rated	Rated	Volt	tage	Wire gauge / size		Cable jacket	Part No.	
	Contacts		current	A/C	D/C	AWG	mm²	cable jacket	Part NO.	
	03 pins	10	1A	60V	60V	26AWG 0.1	0.14	PVC	MA05FAF03ST <u>XX</u> CB14	
	05 pilis	40 03) IA	00V 00V 20A	ZUAVVG	0.14	PUR	MA05FAF03ST <u>XX</u> RB14			
	04 pins	10 02	1.0	COV	601/	26 0000	0.14	PVC	MA05FAF04ST <u>XX</u> CB14	
04 pins	1A	60V	60V	26AWG	0.14	PUR	MA05FAF04ST <u>XX</u> RB14			

Note: \underline{X} refers to cable length

■ Remarks

- Please refer to Page 578 for the Conversion between American Wire Gauge AWG and Wire Cross-section mm².
- Please refer to Page 3 for products' part number encoding rule.

