



M5 Male Molded Cable, Straight

• Connector series: M5


• Gender: Male

• Coding: A

• Locking type: Fix screw • Mounting type: Straight

• Part No.: MA05MAF**STXXXX14

**refers to pins number X refers to cable specification





c**¶**us (€ RoHS ∰



■ General information

Standard:	IEC 61076-2-105			
Ambient temperature:	-40 °C ~ $+80$ °C (fixed installation)			
	-20°C ~ $+80$ °C(flexible installation)			
Connector insert:	TPU			
Connector contacts:	Brass with gold plated			
Connector overmold:	TPU			
Connector nut/screw:	Brass with nickel plated			

Insulation resistance:	≥100MΩ
Contact resistance:	≤5mΩ
Shielding:	Unavailable
IP rating:	IP67 in locked condition
Mating endurance:	>500 cycles

■ Electrical data & Mechanical data

Contacts		Rated	Volt	Voltage		Wire gauge / size		Part No.
		current	A/C	D/C	AWG	mm²	Cable jacket	Part NO.
03 pins	● 1	1A	60V 60V	601/	26AWG	0.14	PVC	MA05MAF03ST <u>XX</u> CB14
	3 • 4			600			PUR	MA05MAF03ST <u>XX</u> RB14
04 pins	1A	601/	601	260006	0.14	PVC	MA05MAF04ST <u>XX</u> CB14	
		IA	60V	60V	26AWG	0.14	PUR	MA05MAF04ST <u>XX</u> RB14

Note: \underline{X} refers to cable length

■ Remarks

- Please refer to Page 578 for the Conversion between American Wire Gauge AWG and Wire Cross-section mm².
- Please refer to Page 3 for products' part number encoding rule.

