



M5 Male Panel Mount, PCB Type, Front fastened

• Connector series: M5

• Gender: Male


• Coding: A


• Locking type: Fix screw

• Mounting type: Front fastened

• Part No.: MB05MBAFF**ST

**refers to pins number











■ General information

Standard:	IEC 61076-2-105
Ambient temperature:	-25℃ ~ +90℃
Connector insert:	TPU
Connector contacts:	Brass with gold plated
Connector nut/screw:	Brass with nickel plated
Seal / O-ring:	Epoxy resin / FKM
	· · ·

Insulation resistance:	≥100MΩ
Contact resistance:	≤5mΩ
Shielding:	Unavailable
IP rating:	IP67 in locked condition
Mating endurance:	>500 cycles


■ Electrical data & Mechanical data

		Contacts	Rated current	Voltage		Dout No.
		termination		A/C	D/C	Part No.
03 pins	3 • 4	PCB version	1A	60V	60V	MB05MBAFF03ST
04 pins	2	PCB version	1A	60V	60V	MB05MBAFF04ST


11


■ Panel Cut-out Dimensions

With bare hole With thread to screw in



■ PCB Layout





4P (Pin OD: Φ 0.5)

■ Remarks

• Please refer to Page 3 for products' part number encoding rule.