


Valve Plug, Female, Field Wirable Assembly, Type C

- Connector series: Valve plug
- Gender: Female
- Construction type: C
- Locking system: Central screw
- Part No.: VCCFAXX**

** refers to pins number




General information

Standard:	Industrial standard
Ambient temperature:	-30 °C~ + 125 °C
Termination:	Screw
Pin dimensions:	4.6x0.5mm, 3.8x0.5mm
Housing color:	Black
Contact bearer material:	PA+GF
Housing material:	PA+GF
Contact:	PS with silver plated
Screw:	Steel with Zn plated
Seal:	FKM/NBR
Gasket:	NBR

Rated voltage:	250V
Rated impulse voltage:	800V
Rated current:	6A
Insulation resistance:	≥ 100MΩ
Contact resistance:	≤ 4mΩ
IP rating:	IP 65 in locked condition
Cable gland:	PG7
Suitable cables(Dia.):	4.0~6.0mm
Conductor size:	0.5mm ²

Electrical data & Mechanical data

Contacts	Part No.
3+PE 	VCCFAXX31

Normal circuit diagram	
.....	00

Remarks

- Please refer to Page 578 for the Conversion between American Wire Gauge AWG and Wire Cross-section mm².
- Please refer to Page 433 for products' part number encoding rule.