

# TS3 SERIES LED TACT SWITCHES

带灯轻触开关



TS3-P-00N-2S



TS3-5SU-2S-1A


## SPECIFICATIONS

Circuit	: SPST
Current Rating	: 50mA
Voltage Rating	: 12VDC
Dielectric withstanding voltage	: 250VAC for 1 minute
Contact Resistance	: 100mΩ Max. (initial)
Insulation Resistance	: 100MΩ Min.
Operating Force	: 180±50gf or 250±50gf
Total Travel	: 0.25±0.1mm
Operating life	: 200,000 Cycles Min
Solder Specifications	: 260°C for 3 Seconds
Function	: Momentary
Operating Temperature	: -20°C ~ +70°C

带灯按钮开关



TS3-6SG-2B-2







TS3-5WR-2B

按钮开关



TS3-00R-12P







金属按钮开关

翘板开关



TS3-P-00G-2S







保险插座

光电触摸开关



TS3-00Y-2S



旋转开关



TS3-00G-3B



TS3-00R-3F






TS3-2BU-3B






TS3-2BG-3F




TS3-3SR-3B-3B




P.C.B. LAYOUT



P.C.B. LAYOUT



CIRCUIT



TS3	P	0 0 R	2 S	0 N
<b>Model</b> 型号	<b>IP Rating</b> 防水等级	<b>Cap Type</b> 上盖形状	<b>Cap Color</b> 上盖颜色	<b>LED Color</b> 灯颜色
	- 不防水 P IP67 防水	0 Without Cap 1 4#±8.0 2 3 4 5 6 7 4#±10.0	0 Without Cap W White 白色 R Red 红色 G Green 绿色 B Black 黑色 A Gray 灰色 Y Yellow 黄色 O Orange 橙色 S Silver 银色 L Natural color 本色上盖 T Transparent 透明	N Without LED R Red 红灯 Y Yellow 黄灯 G Green 绿灯 U Blue 蓝灯 W White 白灯 R/G Red/Green 红绿灯 R/U Red/Blue 红蓝灯
				<b>Key-press Type</b> 按键类型
				2 标准型 3 4 防水专用 12 高温型
				<b>Terminal shape</b> 端子形状
				S 直插型 P 插片型 B 侧向型 F 固定端子型
				<b>Cap Logo</b> 上盖图案
				0 NONE 1 2 3 4 3.0 5 1.0
				<b>Pattern orientation</b> 图案方向
				For Counter N NONE A B C D

带灯轻触开关

带灯按钮开关

按钮开关

金属按钮开关

翘板开关

保险丝座

光电触摸开关

旋转开关